

## Claims:

1. A convertible vehicle (1) with a moving roof (3) having a flexible cover (5), in which the cover (5) is engaged underneath by at least one strap (9), following essentially the course of the roof when the roof (3) is closed, which is secured on rod parts (7; 8) arranged across the roof (3),  
**characterized in that**  
the at least one end (9a) of strap (9) passes through a slit recess (10) of the roof rod (7; 8) and is secured against pulling out from it by an end thickening (11).
2. A convertible vehicle (1) according to Claim 1,  
**characterized in that**  
the end thickening (11) is formed by a loop of the strap (9) stitched around and enclosing a piping.
3. A convertible vehicle (1) according to one of the Claims 1 or 2,  
**characterized in that**  
at least one slit recess (10) is arranged in a front transverse support of roof (3), a so-called roof strut (7).
4. A convertible vehicle (1) according to one of the Claims 1 to 3,  
**characterized in that**  
that the slit recess (10) has a widening (13) on one end that is passed through the end thickening (11).
5. A convertible vehicle (1) according to Claim 4,  
**characterized in that**  
the widening (13) has an essentially round shape with a diameter only slightly greater than that of the end thickening (11).

6. A convertible vehicle (1) according to one of the Claims 1 to 5  
**characterized in that**  
a strap (9) is assigned to each side of the vehicle.
7. A convertible vehicle (1) according to one of the Claims 1 to 6,  
**characterized in that**  
the strap or each strap (9) is free of holes.
8. A convertible vehicle (1) according to one of the Claims 1 to 7,  
**characterized in that**  
the front and rear strap ends (9a) are fastened the same way to different rod parts (7, 8) of roof (3).
9. A moving roof (3) for a convertible vehicle (1) according to one of the Claims 1 to 8.